

Calibration Table SluXXHP

	Disc/Vane type	Spreader height/tilt	Disc Speed	Spread width	Spread Setting	Application rate kg/ha
Bullock Tillage DeLimbe T28.3	275mm 4 Vane	110cm	No.10	12m	Centre	4
		110cm	No.10	12m	Centre	7
		110cm	No.30	24m	Centre	4
		110cm	No.30	24m	Centre	7

	Disc/Vane type	Spreader height/tilt	Disc Speed	Spread width	Spread Setting	Application rate kg/ha
Logic TFS80P	3 Vane	110cm	2700	12m	7	4
		110cm	2700	12m	7	7
		110cm	2700	15m	7	4
		110cm	2700	15m	7	7

	Disc/Vane type	Spreader height/tilt	Disc Speed	Spread width	Spread Setting	Application rate
Spaldings Lehner Super Vario	2 Vane	100cm	3000	12m	1&5	4
		100cm	3000	12m	2&5	7
		100cm	3000	15m	1&5	4
		100cm	3000	15m	2&5	7

	Disc/Vane type	Spreader height/tilt	Disc Speed	Spread width	Spread Setting	Application rate kg/ha
Stocks Ag Fan Jet Pro 65	2 Vane	120cm + 1degree	No.7	12m	Bias 90	4
		120cm + 1degree	No.7	12m	Bias 85	7
		120cm + 1degree	No.12	20m	Bias 90	4
		120cm + 1degree	No.12	20m	Bias 85	7

	Disc/Vane type	Spreader height/tilt	Disc Speed	Spread width	Spread Setting	Application rate kg/ha
Stocks Ag Fan Jet Duo	4 Long Vane	150cm	No.10	24m	Bias 90	4
		150cm	No.10	24m	Bias 90	7
		150cm	No.12	32m	Bias 75	4
		150cm	No.12	32m	Bias 75	7

NB. Information in these tables is only for guidance, settings may vary between machines. Make sure to calibrate individual machines before use.

USE PLANT PROTECTION PRODUCTS SAFELY. ALWAYS READ THE LABEL AND PRODUCT INFORMATION BEFORE USE.

For further information with regard to the warning phrases and symbols for these products please refer to the product labels.

SLUXX HP® is registered trademark of W. Neudorff GmbH KG. SLUXX HP® contains ferric phosphate. MAPP no. 16571

Marketed by: Certis, 3 Riverside, Suite 5, Granta Park, Great Abington, Cambridge CB21 6AD.

Tel: 0845 373 0305 www.certiseurope.co.uk Certis©2019