

Application Settings Guide

This guide advises on applicator settings to give an even spread of pellets across the working width. For specific information on settings to achieve a given dose rate, please refer to the applicator handbook.

	Disc/Vane Type	Spreader Height/ Tilt	Rate Kg/Ha	Disc Speed	Spread Width	Spread Setting
Bullock Tillage DeLimbe T28.3	275mm 4 vane	110cm	4	No.10	12m	Centre
		110cm	7	No.10	12m	Centre
		110cm	4	No.30	24m	Centre
		110cm	7	No.30	24m	Centre

Logic TSF80P	3 vane	110cm	4	2700	12m	7
		110cm	7	2700	12m	7
		110cm	4	2700	15m	7
		110cm	7	2700	15m	7

Spalding Lehner Super Vario	2 vane	110cm	4	3000 rpm	12m	1 & 5
		110cm	7	3000 rpm	12m	2 & 5
		110cm	4	3000 rpm	15m	1 & 5
		110cm	7	3000 rpm	15m	2 & 5

Stocks Ag Fan Jet Pro 65	2 vane	120cm + 1°	4	No.7	12m	Bias 90
		120cm + 1°	7	No.7	12m	Bias 85
		120cm + 1°	4	No.12	20m	Bias 90
		120cm + 1°	7	No.12	20m	Bias 85

Stocks Ag Fan Jet Duo	2 long 2 short	150cm	4	No.10	24m	Bias 90
		150cm	7	No.10	24m	Bias 90
		150cm	4	No.12	32m	Bias 75
		150cm	7	No.12	32m	Bias 75

Settings provided in the spreading tables above are derived from practical tests in the field carried out by SCS Spreader & Sprayer Testing Ltd. Contact info@spreadcheck.com

