

## Application Settings Guide

This guide advises on applicator settings to give an even spread of pellets across the working width. For specific information on settings to achieve a given dose rate, please refer to the applicator handbook.

	Disc/Vane Type	Spreader Height/ Tilt	Rate Kg/Ha	Disc Speed	Spread Width	Spread Setting
<b>Bullock Tillage DeLimbe T28.3</b>	275mm 4 vane	110cm	4	No.10	12m	Centre
		110cm	7	No.10	12m	Centre
		110cm	4	No.30	24m	Centre
		110cm	7	No.30	24m	Centre

<b>Logic TSF80P</b>	3 vane	110cm	4	2700	12m	7
		110cm	7	2700	12m	7
		110cm	4	2700	15m	7
		110cm	7	2700	15m	7

<b>Spalding Lehner Super Vario</b>	2 vane	110cm	4	3000 rpm	12m	1 & 5
		110cm	7	3000 rpm	12m	2 & 5
		110cm	4	3000 rpm	15m	1 & 5
		110cm	7	3000 rpm	15m	2 & 5

<b>Stocks Ag Fan Jet Pro 65</b>	2 vane	120cm + 1°	4	No.7	12m	Bias 90
		120cm + 1°	7	No.7	12m	Bias 85
		120cm + 1°	4	No.12	20m	Bias 90
		120cm + 1°	7	No.12	20m	Bias 85

<b>Stocks Ag Fan Jet Duo</b>	2 long 2 short	150cm	4	No.10	24m	Bias 90
		150cm	7	No.10	24m	Bias 90
		150cm	4	No.12	32m	Bias 75
		150cm	7	No.12	32m	Bias 75

Settings provided in the spreading tables above are derived from practical tests in the field carried out by SCS Spreader & Sprayer Testing Ltd. Contact [info@spreadcheck.com](mailto:info@spreadcheck.com)



USE PLANT PROTECTION PRODUCTS SAFELY. ALWAYS READ THE LABEL AND PRODUCT INFORMATION BEFORE USE.

For further information with regard to the warning phrases and symbols for these products please refer to the product labels.

Ironflexx® is a registered trademark of Neudorff GmbH KG. Ironflexx contains ferric phosphate. MAPP no. 18555.

Marketed by: Certis, 3 Riverside, Suite 5, Granta Park, Great Abington, Cambridge CB21 6AD. Tel: 0845 373 0305 [www.certiseurope.co.uk](http://www.certiseurope.co.uk) Certis® 2020